

# EAT•N

# Powerware

## Powerware 5115 Uninterruptible Power System

Product Focus

500-1400 VA advanced power protection  
for office servers



### Product Snapshot

---

Power Rating:	500-1400 VA
Voltage:	240 VAC
Frequency:	50 Hz
Configuration:	Plug-and-play tower
Topology:	Line-interactive

### Features

- High performance protection
- Software Suite bundled
- ABM™, prolongs battery life by 50%
- Hot-swappable user replaceable batteries
- Australian output sockets eliminate messy adaptors
- Standard USB and RS232 serial ports extend communication capacity

### Options

- ConnectUPS-E external Web/SNMP adaptor

### Typical Applications

- Small office servers
- High-capacity PCs and workstations

Designed to offer advanced power protection for office servers and other critical applications, Powerware 5115 protects your equipment against five of the nine most common power problems that can harm your equipment or result in corrupted data.

In offices a crucial part of the work is stored on servers and reliable shutdown software is needed to ensure that no data is lost even during longer power outages. With Powerware 5115 and LanSafe III protecting the server, business goes on while the UPS invisibly and automatically takes care that no data is lost due to power problems. If a total outage threatens to exceed the system's backup time, LanSafe III software automatically shuts down the entire network in a predefined order.

# Technical Specifications

<b>POWERWARE 5115</b>				
Rating	500VA	750VA	1000VA	1400VA
Part number	51150500A	51150750A	51151000A	51151400A
Capacity (VA/Watts)	500/320	750/500	1000/670	1400/950
Dimensions WxDxH (mm)	150x268x185	150x333x185	150x333x185	150x388x185
Weight (kg)	8	12	13	17
Input connection	IEC320/10A	IEC320/10A	IEC320/10A	IEC320/10A
Output connection	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A
Typical runtime (Full load)	5 min	6 min	5 min	5 min
<b>Operational</b>				
Nominal input voltage (Vac)	240 Vac			
Input voltage range	192 - 288 VAC (+/-20%)			
Operating frequency	50/60 Hz auto sensing			
Input power factor	Same as load			
Output voltage	240 Vac			
Output voltage regulation	216-254 VAC (-10%/+6%) or +/-5% on battery			
Overload capacity	110% 3 min; 150% 10 cycles			
Efficiency	95%			
<b>User interface</b>				
LED	Four LEDs; UPS on, UPS on battery, overload, alarm			
Standard communication ports	1 x RS232 & 1 x USB Port			
Optional	External SNMP adaptor			
<b>Environmental</b>				
Operating temperature	0°C to +40°C			
Storage temperature	-15°C to +55°C			
Altitude	< 3000 m			
Audible noise at 1 metre	< 40dB			
<b>Certification</b>				
Markings	CE/GS/UL/C-Tick			
Safety	EN 50091-1-1 & IEC 609050			
EMC (Class B)	AS62040.2.2001, C-Tick			
<b>Battery Runtimes in minutes</b>				
Load	51150500A	51150750A	51151000A	51151400A
200VA/128W	17	38	41	58
300VA/192W	11	27	28	41
500VA/320W	5	14	15	28
600VA/402W	-	9	10	19
750VA/503W	-	6	8	14
900VA/603W	-	-	6	10
1000VA/670W	-	-	5	8
1200VA/804W	-	-	-	6
1440VA/938W	-	-	-	5

This guide provides typical application information. Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

**HEAD OFFICE**  
Eaton Power Quality Pty Ltd  
10 Kent Road  
Mascot NSW 2020  
Phone: +61 2 9693 9366  
Fax: +61 2 8338 1159

www.powerware.com.au

**SALES OFFICES**  
Queensland  
Phone: +61 7 3891 1211  
Fax: +61 7 3891 2492

Victoria  
Phone: + 61 3 9706 5662  
Fax: + 61 3 9794 9150

South Australia  
Phone: +61 8 8347 3622  
Fax: +61 8 8445 6328

Western Australia  
Phone: +61 8 9240 5655  
Fax: + 61 8 9240 5644

Auckland New Zealand  
Phone: + 64 9 273 3970  
Fax: +64 9 273 3980

Powerware and ABM are trade names, trademarks and/or service marks of Eaton Power Quality Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.

Sales 1300 UPS UPS  
Service 1300 303 059

